



EAGLE FLIGHT® STAINLESS STEEL WHEEL SIMULATORS

Type C INSTALLATION INSTRUCTIONS

Light Duty Over Lug Mounting Using Factory Center Caps

FOR GM VEHICLES HAVING OUTER THREADED LUGNUTS

Front Axle Set

- 2 Front wheel simulators

Rear Axle Set

- 2 Rear wheel simulators

Installation Instructions

- 1 DO NOT REMOVE THE ORIGINAL EQUIPMENT LUG NUTS.**
- 2 REMOVE ANY HUB COVERS AND TRIM RINGS ALREADY ON WHEELS.**
- 3 PLACE WHEEL SIMULATOR ON WHEEL, LINING UP THE HAND OPENINGS OF THE SIMULATOR WITH THOSE IN THE WHEEL.**
- 4 PLACE HUBCOVERS OVER WHEEL SIMULATOR AND TIGHTEN ABS LUG NUT COVERS CAREFULLY IN SEQUENCE ONE TURN AT A TIME. NOTE: FOR DUAL WHEEL APPLICATIONS YOU MUST LINE UP TABS ON THE REAR AXLE COVER WITH SLOTS IN THE REAR SIMULATOR .**
- 5 DO NOT OVER TIGHTEN ABS LUGNUT COVERS.**
- 6 REPEAT STEPS 1 - 5 FOR EACH WHEEL.**

Typical Illustrations Shown

