



INSTALLATION INSTRUCTIONS

For Import Trucks - Front

Note: This system can be installed with the installation tool provided. No other tools are necessary. Do not use power tools for installation. Eagle Flight® recommends storing the tool with the vehicle's tire tool for future use.

- | | |
|---------------------------------------|--------------------------------------|
| • 2 Front wheel simulators | • 2 Left hand jam nuts with SS cover |
| • 2 Right hand Brackets | • 2 Center hub logos |
| • 2 Left hand Brackets | • 1 Installation tool |
| • 2 Right hand jam nuts with SS cover | |

1. **DO NOT REMOVE ANY LUG NUTS.** Over Lug mounted simulators do not require any lug nuts to be removed.
2. Position the simulator over the wheel and align the valve stem and valve stem cutout to determine where the brackets will be placed. Once this is determined, remove simulator.
3. Slide (tap) the brackets under lug nuts on the front . Make sure that you use the left hand threaded parts on the left side and the right hand threaded parts on the right side.
4. Position the simulator and install Jam nuts.
5. Check to be sure the wheel cover is centered on the wheel. Centering of the wheel cover is very important. Failure to center wheel cover may result in throwing the wheel off balance.
6. Complete wheel cover installation by applying hub center emblem.
7. Repeat steps 1 through 6 for the installation of the other wheel.

Typical Front

